

Magnetic Stirring Bars, PTFE

Cylindrical, with pivot ring. For vessels with slightly uneven bottoms. Alnico V magnetic cores. Maximum operating temperature 270 °C.

Ø mm	Length mm	Material sheathing	Form magnetic stirring bars	Max. temp. resistance °C	PK	Cat. No.
3.0	8.0	PTFE	Cylindrical	270	10	4.689 075
4.5	12.0	PTFE	Cylindrical	270	10	4.688 968
4.5	15.0	PTFE	Cylindrical	270	10	4.689 219
6.0	20.0	PTFE	Cylindrical	270	10	4.688 833
6.0	25.0	PTFE	Cylindrical	270	10	4.688 950
6.0	30.0	PTFE	Cylindrical	270	10	4.688 834
6.0	35.0	PTFE	Cylindrical	270	10	4.689 068
8.0	40.0	PTFE	Cylindrical	270	10	4.688 855
8.0	45.0	PTFE	Cylindrical	270	10	4.688 875
8.5	50.0	PTFE	Cylindrical	270	10	4.688 891
8.5	70.0	PTFE	Cylindrical	270	10	4.688 849

Alternativen:

Magnetic Stirring Bars, Cylindrical, PTFE / Bohlender

Magnetic stirring bars, PTFE, octagonal / BRAND

Magnetic stirring bars, PTFE, oval / BRAND