

Membrane filters Nitrocellulose PORAFIL^{®} NC

PORAFIL^{®} NC membranes are made from cellulose nitrate. They are easily wettable and suited for filtration of aqueous solutions. In dry atmosphere these membranes are thermally stable to 125 °C and can be autoclaved at 121 °C.

Ø mm	Pore size µm	Material	Autoclavable	Colour	Max. temp. resistance °C	PK	Cat. No.
13	0.20	Cellulose nitrate (CN)	Yes	White	125	50	4.001 356
25	0.20	Cellulose nitrate (CN)	Yes	White	125	50	4.001 357
47	0.20	Cellulose nitrate (CN)	Yes	White	125	50	4.001 358
50	0.20	Cellulose nitrate (CN)	Yes	White	125	50	4.001 359
90	0.20	Cellulose nitrate (CN)	Yes	White	125	60	4.001 360
100	0.20	Cellulose nitrate (CN)	Yes	White	125	25	4.001 361
142	0.20	Cellulose nitrate (CN)	Yes	White	125	25	4.001 362
220	0.20	Cellulose nitrate (CN)	Yes	White	125	25	4.001 363
13	0.45	Cellulose nitrate (CN)	Yes	White	125	50	4.001 365
25	0.45	Cellulose nitrate (CN)	Yes	White	125	50	4.001 366
47	0.45	Cellulose nitrate (CN)	Yes	White	125	50	4.001 367
50	0.45	Cellulose nitrate (CN)	Yes	White	125	50	4.001 368
90	0.45	Cellulose nitrate (CN)	Yes	White	125	50	4.001 369
100	0.45	Cellulose nitrate (CN)	Yes	White	125	25	4.001 370
142	0.45	Cellulose nitrate (CN)	Yes	White	125	25	4.001 371
220	0.45	Cellulose nitrate (CN)	Yes	White	125	25	4.001 372