

# Membrane filters PORAFIL<sup>&reg;</sup>CM, with grid

Membranes of cellulose mixed esters are ideal for gravimetric analysis. They are particularly suited for aqueous solutions. The hydrophilic membrane is thermally stable to 125 &deg;C and can be autoclaved at 121 &deg;C. This membrane is often used for contamination tests.

Ø mm	Pore size µm	Material	Sterile	Autoclavable	Colour	Colour grid	Max. temp. resistance °C	PK	Cat. No.
47	0.45	Mixed cellulose ester (MCE)	Yes	Yes	White	Black	125	100	4.001 329
50	0.45	Mixed cellulose ester (MCE)	Yes	Yes	White	Black	125	100	4.001 330
50	0.45	Mixed cellulose ester (MCE)	Yes	Yes	Black	White	125	100	4.001 339
50	0.45	Mixed cellulose ester (MCE)	Yes	Yes	Green	Black	125	100	4.001 345
47	0.45	Mixed cellulose ester (MCE)	No	Yes	White	Black	125	100	4.001 350
47	0.45	Mixed cellulose ester (MCE)	No	Yes	Black	White	125	100	4.001 352
47	0.45	Mixed cellulose ester (MCE)	No	Yes	Green	Black	125	100	4.001 354
50	0.45	Mixed cellulose ester (MCE)	No	Yes	White	Black	125	100	4.001 351
50	0.45	Mixed cellulose ester (MCE)	No	Yes	Black	White	125	100	4.001 353
50	0.45	Mixed cellulose ester (MCE)	No	Yes	Green	Black	125	100	4.001 355